BioStar 1,

1 .

.

.

가

PC •

.

.

.

## 1.

1

2.

## 3. BioStar IP

BioStar V1.7	
Eile View Theme Option Administ	trator <u>H</u> elp
Back 画 Forward 🜀 Refresh 🍃	Find User Print
Device	Device
Device BioStar Server 10573[192:168.0.235]	Basic Information         Device ID         10573           Name         10573[192.168.0.235]         Device ID         10573           Firmware         V1.21_130508         Device Type         FSM           Operation Mode         Face         Camera         Network         Access Control         Interphone         Input         Output         Display/Sound         T & A         Wiegand
	[TCP/IP Setting]         Lan Type         Ethernet         Port         1470           WLAN         Preset #1         Change Setting         IP         ID Lise DHCP         INto Lise DHCP
Task Add Device Firmware Upgrade	IP Address         192         168         0         235         Gateway         .
Details	Server     Image: Server       IP Address     192       168     1       90     Server Port       1480
Selected : 10573[192.168.0.235]	[Serial Setting] RS485 RS232
👔 User	Mode Slave   Baudrate 115200  Baudrate Not Use
E Doors	[USB Setting]
Access Control     Monitoring	USB USB Memory © Enable USB port  © Disable USB port  © Disable USB port
Device	
Time and Attendance	Add Modify Delete Apply to Others Apply
Ready	CAP NUM SCRL
BioStar IP	BioStar Server Config .

	BioStar Ser	ver V1.7 (192.168.1.90) Running	Stop
Connec	tion		
0	TCP Port	1480 Thread Count 32	Client Lis
Databas	e		
	Database Type	SQL Server	Ŧ
SQL	Database Name	BioStar	Set Nam
	C Server Authentic	ation 🕼 Windows Authent	ication
	Database Server	MHKIM2-PC\SQLEXP Port	1433
	ID	sa Password	
	Max Connection	1	
SSL			
Sa	OpenSSL Path	C:\OpenSSL\bin\openssl.exe	Browse
	Pass Phrase	****	Change

5.

5.

From: http://kb.supremainc.com/knowledge/ -

Permanent link: http://kb.supremainc.com/knowledge/doku.php?id=ko:1xfaq\_automatic\_time\_synchronization

Last update: 2016/09/02 15:26