1

2021/03/09 1	.3:23
--------------	-------

1/3

.

, BioStar 2

BioStar 2.5.0 가

1. (Setting) > (ALERT)



.

(Device Disconnection Detected)

(Apply)

•

2.

Davice		Doar			Authentication		
2	Device Disconnection Detected	*	Forced door opened	8		1:1 authentication failed	8
1	Device restarted	~	Held door opened	8		1:1 duress authentication succeeded	8
2	RS-485 disconnected		Forced door open alarmed			1:N authentication failed	6
2	Tamper on		Held door open alarmed	Ð		1:N duress authentication succeeded	5
1	Supervised Input (Shart)	~	Anti-passback zone alarm detected	8		Access denied (Invalid access group)	8
	Supervised Input (Open)					Access denied (Disabled user)	5
2	AC Power Failure					Access denied (Expired)	5
						Access denied (Blacklist)	8
						Access denied (Hard Anti-passback)	5
						Access denied (Forced lock schedule)	5
					~	Access denied (Soft anti-passback)	8
						Fake Fingerprint Detected	8

3.

.

(Name)

(Message)	
-----------	--

	Device		Door
2	Device Disconnection Detected	Forced d	loor opened
	Device restarted	8	
	RS-485 disconnected	Alert Mes	ssage ×
	Tamper on	7	
	Supervised Input (Short)	• Name	Device A2 Disconnection
	Supervised Input (Open)	• Message	Device(BioStation A2) is Disconnected
	AC Power Failure	B	
		Sound Na	me None 👻
		Play Optic	None 👻
			Apply Cancel

.

2021/03/09 13:23

3/3



From:

https://kb.supremainc.com/knowledge/ -

Permanent link: https://kb.supremainc.com/knowledge/doku.php?id=ko:how_to_configure_an_alert_pop-up_message_when_a_device_is_disconnected

Last update: 2018/07/12 11:48