

가	1
Initialize	1
Setting Options	2
Scan Card	4
Scan Finger	5
Setting Fingerprint templates and Fingerprint Identified	7
Users finger management (Insert/Update/Delete/Delete all)	9
Data detected (Card/Finger/Input)	11
LED / Output Control	13
Firmware upgrade	14

가

Initialize

```
package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Event;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.callback.Input;
import com.supremainc.sdk.callback.Punch;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    /**
     * DeviceListener receives events about a device.
     */
    private DeviceListener deviceListener = new DeviceListener() {
        @Override
        public void onPunchDetected(Punch data) { }
        @Override
        public void onInputDetected(Input data) { }
        @Override
        public void onEventDetected(Event data) { }
        @Override
        public void onCardScanCompleted(Punch data) { }
        @Override
        public void onFingerprintDetected(Fingerprint data) { }
        @Override
        public void onFingerprintScanCompleted(Fingerprint data) { }
        @Override
        public void onFingerprintIdentified(Fingerprint data) { }
        @Override
        public void onFingerprintScanProgress(int scanTimeout) { }
        @Override
        public void onCardScanProgress(int scanTimeout) { }
    };

    class RunnableImplements implements Runnable {
        @Override
        public void run() {
```

```

        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    /**
     * Set card RF type.
     */
    svpManager.setCardType(Card.RF_HIGH_FREQUENCY);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}
}

```

Setting Options

```

package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.option.CardOption;
import com.supremainc.sdk.option.FingerprintOption;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
};

```

```
class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {

    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        int result = ;

        /**
         * Card option
         */
        CardOption cardOption = new CardOption();
        cardOption.byteOrder = CardOption.BYTE_ORDER_MSB;
        cardOption.scanTimeout = 5;

        result = svpManager.setCardOption(cardOption);

        /**
         * Fingerprint option
         */
        FingerprintOption fingerOption = new FingerprintOption();
        fingerOption.securityLevel =
FingerprintOption.DEFAULT_SECURITY_LEVEL;
        fingerOption.fastMode = FingerprintOption.DEFAULT_FAST_MODE;
        fingerOption.sensitivity =
FingerprintOption.DEFAULT_SENSOR_SENSITIVITY;
```

```
        fingerOption.sensorMode = FingerprintOption.DEFAULT_SENSOR_MODE;
        fingerOption.templateFormat =
FingerprintOption.DEFAULT_TEMPLATE_FORMAT;
        fingerOption.scanTimeout =
FingerprintOption.DEFAULT_SCAN_TIMEOUT;
        fingerOption.lfdLevel = FingerprintOption.DEFAULT_LFD_LEVEL;
        fingerOption.useAdvancedEnrollment = true;
        fingerOption.useBitmapImage = true;

        result = svpManager.setFingerprintOption(fingerOption);
    }
};
}
```

Scan Card

```
package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Punch;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a card scan completed.
         */
        @Override
        public void onCardScanCompleted(Punch data) {
            Log.i(TAG, "result : " + data.result);
            Log.i(TAG, "card number : " + data.displayString);
        }

        /**
         * Called when a card scan progressed.
         */
        @Override
        public void onCardScanProgress(int scanTimeout) {
            Log.i(TAG, "scanTimeout:" + scanTimeout);
        }
    };
}
```

```

    }
};

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    /**
     * Set card RF type.
     */
    svpManager.setCardType(Card.RF_HIGH_FREQUENCY);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        /**
         * Scan card
         */
        int result = svpManager.scanCard();
    }
};
}

```

Scan Finger

```
package com.example.yourapplication;
```

```
import android.graphics.drawable.BitmapDrawable;
import android.graphics.drawable.Drawable;
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a fingerprint scan completed.
         */
        @Override
        public void onFingerprintScanCompleted(Fingerprint data) {
            Log.i(TAG, "result:" + data.result);
            Log.i(TAG, "quality:" + data.quality);

            /**
             * data.template is managed by your application.
             */
            Log.i(TAG, "template:" + data.template.toString());

            if(null != data.image)
            {
                /**
                 * fingerprint bitmap image.
                 */
                Drawable ob = new BitmapDrawable(getResources(),
data.image);
            }

            /**
             * Called when a fingerprint scan progressed.
             */
            @Override
            public void onFingerprintScanProgress(int scanTimeout) {
                Log.i(TAG, "scanTimeout:" + scanTimeout);
            }
        }
    };
};
```

```
class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        /**
         * Scan fingerprint.
         */
        int result = svpManager.scanFingerprint();
    }
};
}
```

Setting Fingerprint templates and Fingerprint Identified

```
package com.example.yourapplication;

import android.graphics.drawable.BitmapDrawable;
import android.graphics.drawable.Drawable;
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.view.View;
```

```
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.model.Finger;
import com.supremainc.sdk.model.FingerList;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a fingerprint identified.
         */
        @Override
        public void onFingerprintIdentified(Fingerprint data) {
            Log.i(TAG, "result:" + data.result);
            Log.i(TAG, "id:" + data.id);
            Log.i(TAG, "templateSize:" + data.templateSize);
            Log.i(TAG, "quality:" + data.quality);
            Log.i(TAG, "fingerprintIndex:" + data.fingerprintIndex);
            Log.i(TAG, "isUpdated:" + data.isUpdated);

            if(null != data.image)
            {
                Drawable ob = new BitmapDrawable(getResources(),
data.image);
            }
        }
    };

    class RunnableImplements implements Runnable {
        @Override
        public void run() {
            /**
             * SDK service run.
             */
            svpManager.run();
        }
    }

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        /**
         * SDK Initialize.
         */
        svpManager.initialize(this, deviceListener);
    }
}
```

```

        Runnable r = new RunnableImplements();
        Thread t = new Thread(r);
        t.start();

        findViewById(R.id.button).setOnClickListener(mClickListener);

        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }

    Button.OnClickListener mClickListener = new View.OnClickListener() {
        public void onClick(View v) {

            /**
             * Fingerprint templates are managed by your application.
             * Template array represents the data received as
            "onFingerprintScanCompleted"
             */
            byte[][] template = new
byte[Finger.TEMPLATE_PER_FINGER][Fingerprint.FINGERPRINT_TEMPLATE_SIZE];

            FingerList fingerList = new FingerList();
            for(int i = 0; i < Finger.MAX_NUM_OF_FINGER; i++)
            {
                Finger finger = new Finger();
                finger.id = i;
                finger.index = (int)(Math.random() *
FingerList.MAX_NUM_OF_FINGER_PER_USER);

                finger.setTemplate(0, template[0]);
                finger.setTemplate(1, template[1]);

                fingerList.addFinger(finger);
            }

            /**
             * Fingerprint matching is done with the set templates.
             * If the fingerprint matches successfully, the
            "onFingerprintIdentified" is called.
             */
            int result = svpManager.setFingerList(fingerList);
        }
    };
}

```

Users finger management (Insert/Update/Delete/Delete all)

```
package com.example.yourapplication;
```

```
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.model.Finger;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
    };

    class RunnableImplements implements Runnable {
        @Override
        public void run() {
            /**
             * SDK service run.
             */
            svpManager.run();
        }
    }

    @Override
    protected void onCreate(Bundle savedInstanceState) {

        /**
         * SDK Initialize.
         */
        svpManager.initialize(this, deviceListener);

        Runnable r = new RunnableImplements();
        Thread t = new Thread(r);
        t.start();

        findViewById(R.id.button).setOnClickListener(mClickListener);

        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }

    Button.OnClickListener mClickListener = new View.OnClickListener() {
        public void onClick(View v) {
            int result = ;
            /**
```

```

        * Fingerprint templates are managed by your application.
        * Template array represents the data received as
"onFingerprintScanCompleted"
        */
        byte[][] template = new
byte[Finger.TEMPLATE_PER_FINGER][Fingerprint.FINGERPRINT_TEMPLATE_SIZE];
        int id = 1000;

        Finger finger = new Finger();
        finger.id = id;
        finger.index = ;
        finger.setTemplate(, template[]);
        finger.setTemplate(1, template[1]);

        /**
         * Insert new finger.
         */
        result = svpManager.insertFinger(finger);

        /**
         * Update new finger.
         */
        result = svpManager.updateFinger(finger);

        /**
         * Delete finger.
         */
        result = svpManager.deleteFinger(finger);

        /**
         * Delete all fingers.
         */
        result = svpManager.deleteAllFinger();
    }
};
}

```

Data detected (Card/Finger/Input)

```

package com.example.yourapplication;

import android.graphics.drawable.BitmapDrawable;
import android.graphics.drawable.Drawable;
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;

```

```
import com.supremainc.sdk.callback.Input;
import com.supremainc.sdk.callback.Punch;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a card detected.
         */
        @Override
        public void onPunchDetected(Punch data) {
            Log.i(TAG, "result : " + data.result);
            Log.i(TAG, "card number : " + data.displayString);
        }

        /**
         * Called when a finger detected.
         */
        @Override
        public void onFingerprintDetected(Fingerprint data) {
            Log.i(TAG, "result:" + data.result);
            Log.i(TAG, "template:" + data.template.toString());
            Log.i(TAG, "quality:" + data.quality);

            if(null != data.image)
            {
                /**
                 * fingerprint bitmap image.
                 */
                Drawable ob = new BitmapDrawable(getResources(),
data.image);
            }
        }

        /**
         * Called when an input detected.
         */
        @Override
        public void onInputDetected(Input data) {
            Log.i(TAG, "result : " + data.result);
            Log.i(TAG, "type : " + data.type);
            Log.i(TAG, "port : " + data.port);
            Log.i(TAG, "status : " + data.status);
        }
    };

    class RunnableImplements implements Runnable {
```

```

        @Override
        public void run() {
            /**
             * SDK service run.
             */
            svpManager.run();
        }
    }

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        /**
         * SDK Initialize.
         */
        svpManager.initialize(this, deviceListener);

        /**
         * Set card RF Type.
         */
        svpManager.setCardType(Card.RF_HIGH_FREQUENCY);

        Runnable r = new RunnableImplements();
        Thread t = new Thread(r);
        t.start();

        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }
}

```

LED / Output Control

```

package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.define.Channel;
import com.supremainc.sdk.define.LedColor;
import com.supremainc.sdk.define.Relay;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";
}

```

```

private DeviceListener deviceListener = new DeviceListener() { };

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        int result = ;
        /**
         * Execute LED action.
         */
        result = svpManager.executeLedAction(LedColor.LED_COLOR_RED);
        /**
         * Execute output action.
         */
        result = svpManager.executeOutputAction(Channel.RELAY_PORT_0,
Relay.ON);
    }
};
}

```

Firmware upgrade

```
package com.example.yourapplication;
```

```
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.define.Channel;
import com.supremainc.sdk.define.LedColor;
import com.supremainc.sdk.define.Relay;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a device event detected.
         */
        @Override
        public void onEventDetected(Event data) {
            Log.i(TAG, "result : " + data.result);
            Log.i(TAG, "code : " + data.code);

            if( data.code == EventCode.EVENT_DEVICE_FIRMWARE_UPGRADED )
            {
                /**
                 * Reboot device.
                 */
                svpManager.rebootDevice();
            }
        }
    };

    class RunnableImplements implements Runnable {
        @Override
        public void run() {
            /**
             * SDK service run.
             */
            svpManager.run();
        }
    }

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        /**
         * SDK Initialize.
         */
    }
}
```

```
        svpManager.initialize(this, deviceListener);

        Runnable r = new RunnableImplements();
        Thread t = new Thread(r);
        t.start();

        findViewById(R.id.button).setOnClickListener(mClickListener);

        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }

    Button.OnClickListener mClickListener = new View.OnClickListener() {
        public void onClick(View v) {
            int result = ;

            /**
             * FTP server option.
             */
            FirmwareOption option = new FirmwareOption();
            option.fileName = "omnis_1.0.0_20181201.bin";
            option.host = "127.0.0.1";
            option.username = "suprema";
            option.password = "suprema";
            option.port = 21;

            /**
             * Connect FTP server.
             */
            result = svpManager.connectFtpServer(option);

            /**
             * Get firmware file list.
             */
            ArrayList<String> fileList = new ArrayList<String>();
            result = mManager.getFirmwareFileList(fileList);

            /**
             * Upgrade firmware.
             */
            result = svpManager.upgradeFirmware(option);
        }
    };
}
```

From:

<http://kb.supremainc.com/svpsdk/> - **SVP Android SDK**

Permanent link:

http://kb.supremainc.com/svpsdk/doku.php?id=ko:quick_guide&rev=1544156082

Last update: **2018/12/07 13:14**