

가 ..... 1

**Initialize** ..... 1

**Setting Options** ..... 2

**Scan Card** ..... 4

**Scan Finger** ..... 5

**Setting Fingerprint templates and Fingerprint Identified** ..... 7

**Users finger management (Insert/Update/Delete/Delete all)** ..... 9

**Data detected (Card/Finger/Input)** ..... 11

**LED / Output Control** ..... 13

**Firmware upgrade** ..... 14

# 가

## Initialize

```
package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Event;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.callback.Input;
import com.supremainc.sdk.callback.Punch;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    /**
     * DeviceListener receives events about a device.
     */
    private DeviceListener deviceListener = new DeviceListener() {
        @Override
        public void onPunchDetected(Punch data) { }
        @Override
        public void onInputDetected(Input data) { }
        @Override
        public void onEventDetected(Event data) { }
        @Override
        public void onCardScanCompleted(Punch data) { }
        @Override
        public void onFingerprintDetected(Fingerprint data) { }
        @Override
        public void onFingerprintScanCompleted(Fingerprint data) { }
        @Override
        public void onFingerprintIdentified(Fingerprint data) { }
        @Override
        public void onFingerprintScanProgress(int scanTimeout) { }
        @Override
        public void onCardScanProgress(int scanTimeout) { }
    };

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        /**
```

```
    * SDK Initialize.
    */
    svpManager.initialize(this, deviceListener);

    /**
     * Set card RF type.
     */
    svpManager.setCardType(Card.RF_HIGH_FREQUENCY);

    /**
     * SDK service run.
     */
    svpManager.run();

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}
}
```

## Setting Options

```
package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.option.CardOption;
import com.supremainc.sdk.option.FingerprintOption;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
    };

    @Override
    protected void onCreate(Bundle savedInstanceState) {

        /**
         * SDK Initialize.
         */
        svpManager.initialize(this, deviceListener);
    }
}
```

```
/**
 * SDK service run.
 */
svpManager.run();

findViewById(R.id.button).setOnClickListener(mClickListener);

super.onCreate(savedInstanceState);
setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        int result = ;

        /**
         * Card option
         */
        CardOption cardOption = new CardOption();
        cardOption.byteOrder = CardOption.BYTE_ORDER_MSB;
        cardOption.scanTimeout = 5;

        result = svpManager.setCardOption(cardOption);

        /**
         * Fingerprint option
         */
        FingerprintOption fingerOption = new FingerprintOption();
        fingerOption.securityLevel =
FingerprintOption.DEFAULT_SECURITY_LEVEL;
        fingerOption.fastMode = FingerprintOption.DEFAULT_FAST_MODE;
        fingerOption.sensitivity =
FingerprintOption.DEFAULT_SENSOR_SENSITIVITY;
        fingerOption.sensorMode = FingerprintOption.DEFAULT_SENSOR_MODE;
        fingerOption.templateFormat =
FingerprintOption.DEFAULT_TEMPLATE_FORMAT;
        fingerOption.scanTimeout =
FingerprintOption.DEFAULT_SCAN_TIMEOUT;
        fingerOption.lfdLevel = FingerprintOption.DEFAULT_LFD_LEVEL;
        fingerOption.useAdvancedEnrollment = true;
        fingerOption.useBitmapImage = true;

        result = svpManager.setFingerprintOption(fingerOption);
    }
};
}
```

## Scan Card

```
package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Punch;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a card scan completed.
         */
        @Override
        public void onCardScanCompleted(Punch data) {
            Log.i(TAG, "result : " + data.result);
            Log.i(TAG, "card number : " + data.displayString);
        }

        /**
         * Called when a card scan progressed.
         */
        @Override
        public void onCardScanProgress(int scanTimeout) {
            Log.i(TAG, "scanTimeout:" + scanTimeout);
        }
    };

    class RunnableImplements implements Runnable {
        @Override
        public void run() {
            /**
             * SDK service run.
             */
            svpManager.run();
        }
    }

    @Override
    protected void onCreate(Bundle savedInstanceState) {
```

```

    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    /**
     * Set card RF type.
     */
    svpManager.setCardType(Card.RF_HIGH_FREQUENCY);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        /**
         * Scan card
         */
        int result = svpManager.scanCard();
    }
};
}

```

## Scan Finger

```

package com.example.yourapplication;

import android.graphics.drawable.BitmapDrawable;
import android.graphics.drawable.Drawable;
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();

```

```
private static final String TAG = "YourApp";

private DeviceListener deviceListener = new DeviceListener() {
    /**
     * Called when a fingerprint scan completed.
     */
    @Override
    public void onFingerprintScanCompleted(Fingerprint data) {
        Log.i(TAG, "result:" + data.result);
        Log.i(TAG, "quality:" + data.quality);

        /**
         * data.template is managed by your application.
         */
        Log.i(TAG, "template:" + data.template.toString());

        if (null != data.image)
        {
            /**
             * fingerprint bitmap image.
             */
            Drawable ob = new BitmapDrawable(getResources(),
data.image);
        }
    }

    /**
     * Called when a fingerprint scan progressed.
     */
    @Override
    public void onFingerprintScanProgress(int scanTimeout) {
        Log.i(TAG, "scanTimeout:" + scanTimeout);
    }
};

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
}
```

```

        svpManager.initialize(this, deviceListener);

        Runnable r = new RunnableImplements();
        Thread t = new Thread(r);
        t.start();

        findViewById(R.id.button).setOnClickListener(mClickListener);

        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }

    Button.OnClickListener mClickListener = new View.OnClickListener() {
        public void onClick(View v) {
            /**
             * Scan fingerprint.
             */
            int result = svpManager.scanFingerprint();
        }
    };
}

```

## Setting Fingerprint templates and Fingerprint Identified

```

package com.example.yourapplication;

import android.graphics.drawable.BitmapDrawable;
import android.graphics.drawable.Drawable;
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.model.Finger;
import com.supremainc.sdk.model.FingerList;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**

```



```

    * Called when a fingerprint identified.
    */
    @Override
    public void onFingerprintIdentified(Fingerprint data) {
        Log.i(TAG, "result:" + data.result);
        Log.i(TAG, "id:" + data.id);
        Log.i(TAG, "templateSize:" + data.templateSize);
        Log.i(TAG, "quality:" + data.quality);
        Log.i(TAG, "fingerprintIndex:" + data.fingerprintIndex);
        Log.i(TAG, "isUpdated:" + data.isUpdated);

        if(null != data.image)
        {
            Drawable ob = new BitmapDrawable(getResources(),
data.image);
        }
    }
};

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {

        /**
         * Fingerprint templates are managed by your application.

```

```

        * Template array represents the data received as
"onFingerprintScanCompleted"
        */
        byte[][] template = new
byte[Finger.TEMPLATE_PER_FINGER][Fingerprint.FINGERPRINT_TEMPLATE_SIZE];

        FingerList fingerList = new FingerList();
        for(int i = ; i < Finger.MAX_NUM_OF_FINGER; i++)
        {
            Finger finger = new Finger();
            finger.id = i;
            finger.index = (int)(Math.random() *
FingerList.MAX_NUM_OF_FINGER_PER_USER);

            finger.setTemplate(, template[]);
            finger.setTemplate(1, template[1]);

            fingerList.addFinger(finger);
        }

        /**
        * Fingerprint matching is done with the set templates.
        * If the fingerprint matches successfully, the
"onFingerprintIdentified" is called.
        */
        int result = svpManager.setFingerList(fingerList);
    }
};
}

```

## Users finger management (Insert/Update/Delete/Delete all)

```

package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.model.Finger;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

```

```
private DeviceListener deviceListener = new DeviceListener() {
};

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {

    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        int result = ;
        /**
         * Fingerprint templates are managed by your application.
         * Template array represents the data received as
"onFingerprintScanCompleted"
         */
        byte[][] template = new
byte[Finger.TEMPLATE_PER_FINGER][Fingerprint.FINGERPRINT_TEMPLATE_SIZE];
        int id = 1000;

        Finger finger = new Finger();
        finger.id = id;
        finger.index = ;
        finger.setTemplate(, template[]);
        finger.setTemplate(1, template[1]);

        /**
```

```
        * Insert new finger.
        */
        result = svpManager.insertFinger(finger);

    /**
     * Update new finger.
     */
    result = svpManager.updateFinger(finger);

    /**
     * Delete finger.
     */
    result = svpManager.deleteFinger(finger);

    /**
     * Delete all fingers.
     */
    result = svpManager.deleteAllFinger();
    }
};
}
```

## Data detected (Card/Finger/Input)

```
package com.example.yourapplication;

import android.graphics.drawable.BitmapDrawable;
import android.graphics.drawable.Drawable;
import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.util.Log;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.callback.Fingerprint;
import com.supremainc.sdk.callback.Input;
import com.supremainc.sdk.callback.Punch;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() {
        /**
         * Called when a card detected.
         */
        @Override
        public void onPunchDetected(Punch data) {
```

```

        Log.i(TAG, "result : " + data.result);
        Log.i(TAG, "card number : " + data.displayString);
    }

    /**
     * Called when a finger detected.
     */
    @Override
    public void onFingerprintDetected(Fingerprint data) {
        Log.i(TAG, "result:" + data.result);
        Log.i(TAG, "template:" + data.template.toString());
        Log.i(TAG, "quality:" + data.quality);

        if(null != data.image)
        {
            /**
             * fingerprint bitmap image.
             */
            Drawable ob = new BitmapDrawable(getResources(),
data.image);
        }
    }

    /**
     * Called when an input detected.
     */
    @Override
    public void onInputDetected(Input data) {
        Log.i(TAG, "result : " + data.result);
        Log.i(TAG, "type : " + data.type);
        Log.i(TAG, "port : " + data.port);
        Log.i(TAG, "status : " + data.status);
    }
};

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);
}

```

```
/**
 * Set card RF Type.
 */
svpManager.setCardType(Card.RF_HIGH_FREQUENCY);

Runnable r = new RunnableImplements();
Thread t = new Thread(r);
t.start();

super.onCreate(savedInstanceState);
setContentView(R.layout.activity_main);
}
}
```

## LED / Output Control

```
package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.define.Channel;
import com.supremainc.sdk.define.LedColor;
import com.supremainc.sdk.define.Relay;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();
    private static final String TAG = "YourApp";

    private DeviceListener deviceListener = new DeviceListener() { };

    class RunnableImplements implements Runnable {
        @Override
        public void run() {
            /**
             * SDK service run.
             */
            svpManager.run();
        }
    }

    @Override
    protected void onCreate(Bundle savedInstanceState) {
```

```

    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
        int result = ;
        /**
         * Execute LED action.
         */
        result = svpManager.executeLedAction(LedColor.LED_COLOR_RED);
        /**
         * Execute output action.
         */
        result = svpManager.executeOutputAction(Channel.RELAY_PORT_0,
Relay.ON);
    }
};
}

```

## Firmware upgrade

```

package com.example.yourapplication;

import android.support.v7.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;

import com.supremainc.sdk.SvpManager;
import com.supremainc.sdk.define.Channel;
import com.supremainc.sdk.define.LedColor;
import com.supremainc.sdk.define.Relay;
import com.supremainc.sdk.service.DeviceListener;

public class MainActivity extends AppCompatActivity {

    SvpManager svpManager = new SvpManager();

```

```
private static final String TAG = "YourApp";

private DeviceListener deviceListener = new DeviceListener() {
    /**
     * Called when a device event detected.
     */
    @Override
    public void onEventDetected(Event data) {
        Log.i(TAG, "result : " + data.result);
        Log.i(TAG, "code : " + data.code);

        if( data.code == EventCode.EVENT_DEVICE_FIRMWARE_UPGRADED )
        {
            /**
             * Reboot device.
             */
            svpManager.rebootDevice();
        }
    }
};

class RunnableImplements implements Runnable {
    @Override
    public void run() {
        /**
         * SDK service run.
         */
        svpManager.run();
    }
}

@Override
protected void onCreate(Bundle savedInstanceState) {
    /**
     * SDK Initialize.
     */
    svpManager.initialize(this, deviceListener);

    Runnable r = new RunnableImplements();
    Thread t = new Thread(r);
    t.start();

    findViewById(R.id.button).setOnClickListener(mClickListener);

    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_main);
}

public void ftpUpgrade()
{
    int result = ;
}
```



```
/**
 * FTP firmware option.
 */
FirmwareOption option = new FirmwareOption();
option.type = FirmwareOption.FTP_UPGRADE;
option.fileName = "omnis_1.0.0_20181201.bin";
option.host = "127.0.0.1";
option.port = 21;
option.username = "suprema";
option.password = "suprema";

/**
 * Connect FTP server.
 */
result = svpManager.connectFtpServer(option);

/**
 * Get firmware file list.
 */
ArrayList<String> fileList = new ArrayList<String>();
result = mManager.getFirmwareFileList(fileList);

/**
 * Upgrade firmware.
 */
result = svpManager.upgradeFirmware(option);

/**
 * Disconnect FTP server.
 */
result = svpManager.disconnectFtpServer();
}

public void usbUpgrade()
{
    int result = ;
    /**
     * USB firmware option.
     */
    FirmwareOption option = new FirmwareOption();
    option.type = FirmwareOption.USB_UPGRADE;
    option.fileName = "omnis_1.0.0_20181201.bin";

    /**
     * Upgrade firmware.
     */
    result = svpManager.upgradeFirmware(option);
}

Button.OnClickListener mClickListener = new View.OnClickListener() {
    public void onClick(View v) {
```

```
    /**
     * FTP firmware upgrade.
     */
    ftpUpgrade();

    /**
     * USB firmware upgrade.
     */
    usbUpgrade();
};
}
```

From:

<http://kb.supremainc.com/svpsdk/> - **SVP Android SDK**

Permanent link:

[http://kb.supremainc.com/svpsdk/doku.php?id=ko:quick\\_guide&rev=1544503832](http://kb.supremainc.com/svpsdk/doku.php?id=ko:quick_guide&rev=1544503832)

Last update: **2018/12/11 13:50**